



## ENAIKOON buzzer

Audio signal buzzer for audible signalling and event confirmation

This inexpensive buzzer can be connected to any digital output of any ENAIKOON tracking device.

This can be used for audio signals and confirmation of events.

There are countless options to configure the ENAIKOON tracking devices in combination with the ENAIKOON buzzer.

### Technical data

- volume 75 dB
- power consumption 20 mA
- frequency 400 Hz
- tonality continuous tone
- size 33 x 15.5 x 15.6 mm (1.3 x 0.61 x 0.61 in)
- cable length 150 mm (5.91 in)
- RoHS conform yes
- input voltage 9 V to 15 V DC or 16 V to 28 V DC
- temperature range -40 °C to +70 °C (-40 °F to +158 °F)

### Typical applications

- ENAIKOON buzzer provides audible warnings when your predefined speed is exceeded
- alerts when a certain threshold is met indicating an unexpected event (e.g. opening of doors, fuel theft, etc.)
- ENAIKOON buzzer gives audible warnings when entering or leaving defined "geofence" areas

### Applications in conjunction with ENAIKOON driver-id

- ENAIKOON buzzer creates short audible signals whenever an ENAIKOON driver-id reader successfully scans an ENAIKOON iButton
- ENAIKOON buzzer sounds an audible warning from the moment the vehicle ignition is turned on until the ENAIKOON iButton of the driver has been identified by the ENAIKOON driver-id reader

## Products and prices

Product	Part no.	Product description	Price
ENAIKOON buzzer	ZUB-09-32	Buzzer for audio signalling and confirmation of events, including the configuration of the ENAIKOON tracking device	€ 19.90